

Product data sheet

Modular HDMI and USB socket 180 degree, unshielded



Reference number

HDMI+USB-002-01

Modular 180 degree RJ45 HDMI and USB keystone socket, unshielded

HDMI socket:

- no effect on the signal and therefore supports all high speed HDMI features, including 3D Video, 4K video and high definition multichannel compressed audio
- the design double HDMI headers, which is convenient for using (female-female)

USB socket:

- female-female socket

with supporting frame, screw fixing only

Polycarbonate plastic (scratch-proof, PC), glossy

Colour printing possible

Consider bending radius and various plug types. Ensure sufficient installation space.

Centre plates colour, EAN code:

- E/B - White, 4770025856055
- E/S - Sandy, 4770025870778
- E/R - Brown, 4770025874202
- E/Mt - Metallic, 4770025854617
- E/J - Black, 4770025868201
- E/Ch - Champagne, 4770025864579

Technical specifications

HDMI:

Electrical

2.0 standard

Voltage rating AC 125V

Current rating 1.5 AMPS

Insulation resistance 500 MΩ Min

HDMI™ type A 2.0 (4K @ 50/60 Hz, Full HD @ 48Hz 3D, HDR Video)

Contact material

Wire

gold-plated phosphor bronze 0.45 dia
AWG 24-26

USB:

3.0 High Speed

Holder for connector / module

Protection

Dept

Metal mounting plate

IP 20

30mm

