


Product data sheet

SCHUKO® socket with 2 USB ports



Reference number

IUK-3-01 (G610)

Flush mount, SCHUKO® socket with earth contacts with smart USB charger for electronic devices with 1 port “type A”, and 1 port “type C”, without frame

SCHUKO® socket outlet;
USB ports type A+C;
screw fixing, with spreader claws.

Intended use

- battery charging station for mobile devices with USB-A or USB-C connection;
- installation in flush box according: DIN 49073 (dept ~35mm), or EN 60670-1;
- socket outlet with earth contacts, 16A;
- charging current: max. 3400 mA;
- operation with suitable cover.

Product characteristics

- Ideal for cafés, hotels or, own four walls, office – wherever you need new energy for your smartphone or tablet quickly: single USB-A or USB-C port. Depending on the connected mobile device, increases the voltage level.
- Support the following standards: Apple 2.4 A, Samsung adaptive charging;
- Installation into multiple frame (1-6 place) with other devices possible;
- Polycarbonate plastic (scratch-proof, PC).

Polycarbonate plastic (scratch-proof, PC). Surface sprayed manually by Alpcryl Emallack paint, (developed in Switzerland), and laked with matt lack. Paint has high UV resistance, is flame resistant according to DIN EN13501-1 and chemically resistant according to DIN 68861/1B;

Centre plates colour, EAN code:

IUK-3-01.R/ON31 - mat brown, 4770025002308; package barcode 4770025002315;
IUK-3-01.R/ONC - mat cream, 4770025002322; package barcode 4770025002339;
IUK-3-01.R/ON59 - mat black, 4770025002346; package barcode 4770025002353;

Technical specifications:

Input voltage, frequency	AC 220 ... 250 V ~ +- 10% , 50/60 Hz
Output current, SCHUKO® socket	AC 220 ... 250 V ~, 16A
Output current USB charger (both using)	max. 3400mA, 17W max. efficiency 83%
USB-A charger only	2.4A max
USB-C charger only	3.0A max
Connection mode:	
single wire	screw terminals, for wires 2,5 ² - 4mm ²
stranded without ferrule	screw terminals, for wires 2,5 ² - 4mm ²
Screw tightening torque max 1,2Nm	according to standart 884-1 IEC:1994
Storage/transport temperature	-20 ... +40 °C
Ambient temperature	-5 ... +35 °C
Centre plates material	polycarbonate (PC)
Customs tariff number	8536699008

