



Product data sheet

SCHUKO® socket with 2 USB ports



Reference number

IUK-3-01.EPSILON (G610)

Flush mount, SCHUKO® socket with earth contacts with smart USB charger for electronic devices with 1 port "type A", and 1 port "type C", without frame

SCHUKO® socket outlet;
USB ports type A+C;
screw fixing, with spreader claws.

Intended use

- battery charging station for mobile devices with USB-A or USB-C connection;
- installation in flush box according to DIN 49073 (dept ~35mm);
- SCHUKO® socket outlet with earth contacts, 16A;
- charging current: max. 3400 mA;
- operation with suitable EPSILON serie cover.

Product characteristics

Ideal for cafés, hotels or, own four walls, office – wherever you need new energy for your smartphone or tablet quickly: single USB-A or USB-C port.
Depending on the connected mobile device, increases the voltage level.

- Support the following standards: Apple 2.4 A, Samsung adaptive charging;
- Installation into multiple frame (1-6 place) with other devices possible;
- Polycarbonate plastic (scratch-proof, PC).

Centre plates colour, EAN code:

- IUK-3-01.E/B - White, 4770025002360, 10pc. package 4770025002377;
- IUK-3-01.E/S - Sandy, 4770025002384, 10pc. package 4770025002391;
- IUK-3-01.E/R - Brown, 4770025002445, 10pc. package 4770025002452;
- IUK-3-01.E/Mt - Metallic, 4770025002407, 10pc. package 4770025002414;
- IUK-3-01.E/J - Black, 4770025002421, 10pc. package 4770025002438;
- IUK-3-01.E/Ch - Champagne, 4770025002469, 10pc. package 44770025002476;

Technical specifications:

Input voltage, frequency	AC 220 ... 250 V ~ +- 10% , 50/60 Hz
Output current, SCHUKO® socket	AC 220 ... 250 V ~, 16A
Output current USB charger (both using)	max. 3400mA, 25W. Efficiency 83%
USB-A charger only	2.4A max
USB-C charger only	3.0A max
Connection mode:	
single wire	screw terminals, for wires 2,5 ² - 4mm ²
stranded without ferrule	screw terminals, for wires 2,5 ² - 4mm ²
	tightening torque max 0,5Nm
Storage/transport temperature	-20 ... +40 °C
Ambient temperature	-5 ... +35 °C
Centre plates material	polycarbonate (PC)
Customs tariff number	8536699008

